# WTAL15

| | | | |
|---|---|---|---|
| **PRODUCT CODE** | OSFB04 | **CATEGORY** | Architectural Window Film |
| **SERIES** | Outside Install Series | **SPECIFICATION** | 1.524*30 |

## PHYSICAL & TECHNICAL PARAMETERS

| PARAMETER | VALUE |
|---|---|
| **Width** | 1.52 m |
| **Length** | 30.00 m |
| **Contact Angle** | 102 |

## DESCRIPTION

WTAL15 is a premium architectural window film engineered for solar control, energy efficiency, and enhanced privacy. Designed for professional installation on commercial and residential windows.

**Specifications:**

Size: 1.524*30

Product Code: OSFB04

## ADDITIONAL PARAMETERS

| | |
|---|---|
| **Visible Light Transmittance** | 15 |
| **Visible Light Reflectance (External)** | 56 |
| **Visible Light Reflectance (Internal)** | 55 |
| **Infrared Rejection** | 80 |
| **UV Rejection** | 99 |
| **Shading Coefficient** | 0.22 |
| **Heat Transfer Coefficient (U-Value)** | 2.4 |
| **Total Solar Energy Rejected** | 79 |
| **Surface Hardness** | 2 |
| **Haze** | 3 |
| **Thickness** | 2.5 |

## APPLICATIONS

Architectural Window Film Installation

**Disclaimer:** The information contained in this document is based on current knowledge and experience and is provided in good faith. It is the reader's responsibility to determine the suitability of the product for their intended application. Specifications are subject to change without notice.